

# Kit 02/05

## Automatic pump control

### Applications


Compact pressurisation equipment which, when fitted onto a suitable pump, automatically supplies water on demand. Also available with dry run protection, pressure gauge and diaphragm.

### Avantages


Compact design eliminating the need for pressure vessels, separate pressure switches, non return valves, pressure gauges and dry run protection devices.

### Features

Pressure gauge.  
Fully automatic electronic control.  
Reset button.  
Built-in non return valve.



	A	B	Kg
Kit 02	240	135	1,4



	A	B	C	Kg
Kit05	214	127	154	1,4



Kit02/3



Kit05


TECHNICAL FEATURES			
Model	Kit 05	Kit 02/3	Kit02/4
<b>Voltage</b>	230 V	230 V	230 V
<b>Maximum Amperage</b>	10 A	10 A	10 A
<b>Hz</b>	50/60 Hz	50/60 Hz	50/60 Hz
<b>Protection</b>	IP 55	IP 55	IP 55
<b>Maximum pressure</b>	10 Bar	7.5 Bar	7.5 Bar
<b>Maximum static pressure</b>	1.5 Bar	1.0 Bar	1.0 Bar
<b>Starting pressure</b>	1.5 - 2.5 Bar adjustable	1.5 Bar	2.4 Bar
<b>Stopping pressure</b>	Maximum pressure of the pump		
<b>Differential pressure</b>	≥ 0.5 Bar	≥ 0.7 Bar	≥ 0.7 Bar
<b>Maximum flow</b>	10 m <sup>3</sup> /h	8 m <sup>3</sup> /h	8 m <sup>3</sup> /h
<b>Maximum building height</b>	2mtrs under starting pressure of pump	12 mtrs	20 mtrs
<b>Maximum temperature</b>	60°C	60°C	60°C
<b>Ø Inlet connection</b>	1" male	1" male	1" male
<b>Ø Outlet connection</b>	1" male	1" female	1" female